DATA SHEET

Pluggable Multi-pole SPD

ProTec T2-CM-4+0-L-E(-R)

Class II • Class III • Type 2 • Type 3

Location of Use: Sub-distribution Boards
Network Systems: TN-S, TN-C,IT* (only 440)
Mode of Protection: L-PE, L-PEN, N-PE
IEC/EN Category: Class II+III / Type 2+3
Housing: Pluggable Design
Compliance: IEC 61643-11:2011
EN 61643-11:2012+A11:2018

Technical Data

ProTec T2-CM-xxx-4+0-L-E(-R)			275	440
Electrical				
Nominal AC Voltage (50/60 Hz)		U_o	230 V	230 V
Maximum Continuous Operating Voltage (AC)		U_c	275 V	440 V
Nominal Discharge Current (8/20 µs)		I_n	10 kA	
Maximum Discharge Current (8/20 µs)		I_{max}	20 kA	
Voltage Protection Level for Type 2+3		U_p	1200 V	1700 V
Voltage Protection Level for Type 3 only		U_p	1000 V	1400 V
Open Circuit Voltage of Combination Wawe Generator (1.2/50 µs)		U_{oc}	6 kV	
Short Circuit Current of Combination Wawe Generator (8/20 µs)		I_{cw}	3 kA	
Response Time		t_A	< 25 ns	
Overcurrent Protection (max)			100 A gG	
Short-Circuit Current Rating		I_{SCCR}	25 kA	
TOV Withstand 5s		U_T	335 V	440 V
TOV 120 min		U_T/mode	440 V / Safe Fail	440 V / Withstand
Number of Ports			1	
Additional Electrical Parameters *(Tests performed within Raycap testing laboratory only)*				
Residual Voltage at 5 kA (8/20 µs)		U_{res}	1000 V	1500 V
Overcurrent Protection (min)			40 A gG	
Mechanical & Environmental				
Temperature Range		T_a	-40 °C to +85 °C	
Permissible Humidity		RH	5%...95%	
Altitude (max)			6562 ft [2000 m]	
Terminal Screw Torque	(L, N)	M_{max}	10 lbf·in [1.2 Nm]	
	(PE)	M_{max}	17 lbf·in [2.0 Nm]	
Conductor Cross Section (max)	(L, N)		8 AWG (Solid, Stranded) / 10 AWG (Flexible)	
			10 mm² (Solid, Stranded) / 6 mm² (Flexible)	
	(PE)		2 AWG (Solid, Stranded) / 4 AWG (Flexible)	
			35 mm² (Solid, Stranded) / 25 mm² (Flexible)	
Mounting			35 mm DIN Rail, EN 60715	
Degree of Protection			IP 20 (built-in)	
Thermal Protection			Yes	
Fault Indication			Red Flag	
Remote Contacts (RC)			Optional	
RC Switching Capacity			AC: 250 / 0.5A; DC: 60V / 0.1A	
RC Terminal Cross Section (max)			13 AWG [1.5 mm²]	
RC Terminal Screw Torque		M_{max}	3.5 lbf·in [0.4 Nm]	

**Only applicable for SPD with Uc 440 V to IT power systems where the earth on the distribution transformer is interconnected with the earth on the consumer side (RE=RA in Figure 44.A1 of IEC 60364-4-44:2018).*

RoHS COMPLIANT CE

Raycap

www.raycap.com

Information contained in this document is subject to change at any time without notice.

Internal Configuration

Legend

L	*Line Conductor Terminal*
N	*Neutral Conductor Terminal*
⏚	*PE Conductor Terminal*
RC	*Remote Contacts Terminal*
TD	*Thermal Disconnector*



ProTec T2-CM-xxx-4+0-L-E(-R)

Order Information

Order Code	275	440
ProTec T2-CM-xxx-4+0-L-E	515 603	515 605
ProTec T2-CM-xxx-4+0-L-E-R (with remote contact)	515 604	515 606
ProTec T2-CM-xxx-L-E-P (plug)	515 667	515 668

Dimensions & Packaging



Complete Unit

ProTec T2-CM-xxx-4+0-L-E		**275**	**440**
Weight	pounds [grams]	.618 [281]	.654 [297]
ProTec T2-CM-xxx-4+0-L-E-R			
Weight	pounds [grams]	.632 [287]	.667 [303]
DIN 43880 Dimension		2 TE / 1.42" [36 mm]	
Packaging Dimensions (H × W × L)		3.2 × 1.7 × 4.6" [83.5 × 44 × 117 mm]	
Standard Order Quantity		8 Units	

Spare plug



Single Unit

ProTec T2-CM-xxx-L-E-P		**275**	**440**
Weight	pounds [grams]	.173 [78.5]	.190 [86.5]
DIN 43880 Dimension		1 TE / .70" [18 mm]	
Packaging Dimensions (H × W × L)		2.5 × 1.8 × 8.7" [64 × 45 × 220 mm]	
Standard Order Quantity		24 Units	

© 2022 Raycap All rights reserved.