DATA SHEET

Overvoltage Protection

SafeTec T2 1+1

Class II • Type 2 • Type 1CA

Location of Use: Sub-distribution Boards
Network Systems: TT, TN-S
Mode of Protection: L-N, N-PE
IEC/EN/UL Category: Class II / Type 2 / Type 1CA
Safety: Current Limiting Technology
Housing: Pluggable Design
Compliance: IEC 61643-11:2011
EN 61643-11:2012+A11:2018
UL 1449 5th Edition

Technical Data

SafeTec T2-xxx-3+1(-R)			300	350
IEC Electrical				
Nominal AC Voltage (50/60Hz)		U_o/U_n	240 V	277 V
Maximum Continuous Operating Voltage (AC)	(L-N)	U_c	300 V	350 V
	(N-PE)	U_c	305 V	305 V
Nominal Discharge Current (8/20 µs)	(L-N)/(N-PE)	I_n	20 kA/40 kA	20 kA/40 kA
Maximum Discharge Current (8/20 µs)	(L-N)/(N-PE)	I_{max}	50 kA/65kA	50 kA/65kA
Voltage Protection Level	(L-N)/(N-PE)	U_p	1650 V/1500 V	1750 V/1500 V
Follow Current Interrupt Rating	(N-PE)	I_{fi}	100 A	
Response Time	(L-N)/(N-PE)	t_A	< 25 ns/< 100 ns	
Overcurrent Protection (max)			315 A/250 A gG	
Short-Circuit Current Rating (AC)	(L-N)	I_{SCCR}	25 kA/50 kA	
TOV Withstand 120min	(L-N)	U_T	442 V	529 V
TOV Withstand 200ms	(N-PE)	U_T	1200 V	
Number of Ports			1	
UL Electrical				
Maximum Continuous Operating Voltage (AC)	(L-N)/(N-PE)	MCOV	300 V/305 V	350 V/305 V
Voltage Protection Rating	(L-N)/(N-PE)	VPR	1200 V/1000 V	1200 V/1000 V
Nominal Discharge Current (8/20 µs)	(L-N)/(N-PE)	I_n	20 kA/20 kA	
Short-Circuit Current Rating (AC)	(L-N)	SCCR	150 kA	200 kA
Additional Electrical Parameters *(Tests performed within Raycap testing laboratory only)*				
Residual Voltage at 5 kA (8/20 µs)	(L-N)/(N-PE)	U_{res}	1000 V/305 V	1300 V/305 V
Overcurrent Protection (min)			80 A gG	
Mechanical & Environmental				
Operating Temperature Range		T_a	-40 °F to +185 °F [-40 °C to +85 °C]	
Permissible Operating Humidity		RH	5%...95%	
Altitude (max)			13123 ft [4000 m]	
Terminal Screw Torque		M_{max}	40 lbf·in [4.5 Nm]	
Conductor Cross Section (max)			2 AWG (Solid, Stranded) / 4 AWG (Flexible)	
			35 mm² (Solid, Stranded) / 25 mm² (Flexible)	
Mounting			35 mm DIN Rail, EN 60715	
Degree of Protection			IP 20 (built-in)	
Housing Material			Thermoplastic: Extinguishing Degree UL 94 V-0	
Thermal Protection			Yes	
Operating State / Fault Indication			Green Flag / Not Green Flag	
Remote Contacts (RC)			Optional	
RC Switching Capacity			AC: 250 V/1 A, 125 V/1 A; DC: 48 V/0.5 A, 24 V/0.5 A, 12 V/0.5 A	
RC Conductor Cross Section (max)			16 AWG (Solid) / 1.5 mm² (Solid)	

RoHS COMPLIANT

Information contained in this document is subject to change at any time without notice.

Internal Configuration

Legend

L	*Line Conductor Terminal*
N	*Neutral Conductor Terminal*
⏚	*PE/G Conductor Terminal*
RC	*Remote Contacts Terminal (Optional)*
TC	*Thermal Control Function*
TD	*Thermal Disconnector*



SafeTec T2-xxx-3+1(-R)

Order Information

Order Code	300	350
SafeTec T2-xxx-3+1	59.0198	59.0200
SafeTec T2-xxx-3+1-R (with remote contacts)	59.0199	59.0201
SafeTec T2-xxx-P (plug L-N)	59.0127	59.0128
SafeTube T2-40-P (plug N-PE)	59.0274	59.0274

Dimensions & Packaging

inches [mm]



Complete Unit

SafeTec T2-xxx-3+1		**300**	**350**
Weight	pounds	1.066	1.119
	grams	483	507
SafeTec T2-xxx-3+1-R			
Weight	pounds	1.077	1.130
	grams	488	512
DIN 43880 Dimension		4 TE / 2.84" [72]	
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 115 x 352 mm]	
Standard Order Quantity		4 Units	

Spare Plug



Single Unit

SafeTec T2-xxx-P		**300**	**350**
Weight	pounds	.146	.163
	grams	66	74
SafeTube T2-40-P		**40**	
Weight	pounds	.093	
	grams	42	
DIN 43880 Dimension		1 TE / .71" [18]	
Packaging Dimensions (H x W x L)		3.2 x 4.5 x 12" [83 x 116 x 305 mm]	
Standard Order Quantity		24 Units	

© 2024 Raycap All rights reserved.